



# PRIMERKRON PU

**Polyurethane based adhesion promoter  
for porous substrates**



**PRIMERKRON PU** is a polyurethane based Primer for Krongum products such as **KRONPOLYUREA AB, POLYFLEXKRON PU, EPOXYKRON Road AB** and **EPOXYKRON FLOOR AB** having a 45% dry content and a specific gravity of 1.02 g/ml .

**APPLICATION FIELDS**

- Pre-treatment for concrete, lightweight concrete, brickwork, wooden substrates.

**SURFACE PREPARATION and APPLICATION**

- Ensure that loose parts, dust, oil and grease are removed. Carefully clean the surfaces, which must be solid, even and dry.
- Keep the packaging well closed until the moment of use.
- Do not use **PRIMERKRON PU** direct from the original packaging.
- Pour the required amount of product from its original packaging into a clean glass or metal (tin) container, which must be used within 30 minutes and immediately close the original packaging. Apply the primer with a clean brush in a thin coat, forming a continuous film at a temperature between +5°C and +30°C.

**DRYING TIME**

- Min. 1 hour and no longer than 3 hours

**COVERAGE**

- The coverage depends on the type and porosity of the substrate and will be around 120 gr/m<sup>2</sup>

**PACKAGING AND STORAGE**

- **PRIMERKRON PU** is packed in 1,0 or 0,5 Kg tin with a shelf-life of 6 months if stored in dry places at temperatures between +5°C and +30°C

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. Krongum Solutions S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Krongum Solutions S.r.l. disclaims any liability arising from non-compliance with the instructions given in this technical data sheet and with the guidelines specified in the safety data sheets. Clients are kindly requested to verify that they are in possession of the current edition.

